

Q-CashExterior 35

Why not let customers handle deposits, withdrawals and bill payment 24/7?

Through-the-wall multi-function outdoor ATM



Fast facts

Securely holds up to 15,000 banknotes and/or tickets and vouchers

Accommodates various banknote sizes and denominations

Safeguards customer information with recessed keyboard and card reader

Envelope deposit

Passbook or statement printing

Standard 12 mm or CEN IV safe

Intuitive user interface

Optional ink-staining technology

Wide variety of options for customisation

EMV approved

Application

The Q-CashExterior™ 35 is a multi-function automated teller machine in the BANQIT family of ATM products. This high-performance through-the-wall ATM is ideal for banks, retailers and cash-in-transit companies.

Easily installed at almost any outdoor location, the Q-CashExterior 35 offers the convenience of automated teller services 24/7. Compact and rugged in design, the unit delivers reliable performance even in the harshest climates.

How it works

Based on state-of-the-art technology, the Q-CashExterior 35 provides secure and reliable deposit and dispense services.

At the heart of the system is the high-speed cash dispenser that delivers up to 100 banknotes in a single bundle. Capable of housing up to five adjustable cassettes, the system has a total cassette capacity of 15,000 banknotes. In addition to basic deposit and dispense services, the Q-CashExterior 35 supports these functions:

Barcode scanning. An optional barcode reader integrated into the front fascia enables 24/7 self-service bill payment. Bi-directional scanning ensures ease of operation.

Envelope deposit. An optional depository unit presents an empty envelope and accepts a filled envelope through the same slot in the front fascia. The machine then prints, stacks and stores the envelope in a lockable cassette.

Passbook processing. An optional processing system automatically updates passbooks. Magnetic stripe and barcode identify the passbooks and account numbers. The system supports various passbook sizes, automatic page turning and book retract.

Benefits

- Maximum capacity using minimal space
- Efficient cash handling
- Reduced cash handling costs
- Improved operational efficiency
- Low cost of ownership
- Increased customer satisfaction, thanks to easy-to-access multi-function services

Q-CashExterior 35

System features

Hardware	
Note and media dispenser	One to five cassettes housed in a 12 mm or CEN IV safe. Polycarbonate multimedia cassette with 350 mm capacity. Single note reject and bundle retract into separate compartments. Up to 100 banknotes in a bundle presentation. Friction-feed technology. Picking speed up to 15 banknotes per second.
Display	12.1" SVGA vandal-resistant colour LCD. Resolution: Supports up to 1024 x 768 pixels. 4 plus 4 menu keys. OSD support. Privacy/anti-glare filter. Optional sunlight viewable version.
Thermal receipt printer	Graphics printer with loop presenter and top of form. Paper rolls: Max. diameter 203 mm; inner diameter 25.4 mm. Max. paper length: Approx. 480 m. Paper width: 80 mm (48 columns). Easy paper loading. Mini-statement width: 80 columns x 20 rows.
Journal	Electronic journal and/or printer journal. Journal matrix printer paper rolls: Max. diameter 83 mm; inner diameter 12.5 mm. Max. paper length: Approx. 60 m. Paper width: 76 mm (40 columns).
Card reader	Motorised card reader in recessed position: Reads tracks 1-3 (LoCo/HiCo); writes tracks 1-3 (LoCo); smart card support. EMV4 Level 1 approved. Anti-skimming. Card return at power failure. Lockable card capture bin. Bin capacity: 20 cards.
Keyboard	16-key tamper-resistant metal keyboard in recessed position. Secure Encrypting PIN Pad (EPP). DES, 3DES, MAC RSA, VISA PED certified. High performance for fast EMV transactions. Country-specific character sets available. Upgradeable functionality.
Physical security	Standard 12mm or CEN IV safe. Mechanical locks and/or dial lock. Door sensors. Prepared for alarm equipment. Options: Time lock and advanced electronic ink dye system.
Dimensions	Height: 1697 mm (1865 mm with passbook/statement printer). Width: 666 mm (Standard safe). Depth: 775 mm.
Options	
Envelope depository	Envelope dispense and deposit in same slot. 180 mm envelope deposit capacity. Max. envelope size: 120 x 230 mm. Integrated envelope ink jet printer. 80 characters per line. End of ink recognition.
Barcode reader	CCD type scanning. Supports EAN/UPC, Code 128, Code 39, Codabar, Interleaved 2 of 5 and most other barcode standards.
Passbook printer	Bi-directional page turning. 24-pin matrix printer supporting horizontally folded passbooks. Magnetic stripe or barcode recognition. Supports various passbook sizes. Print speed up to 384 cps.
Statement printer	Thermal printer. Supports up to A4. Loop presenter. Optional graphics.
Other options	Speaker and earphone connector. Camera. Braille. Remote status indicator (RSI). Burglar alarms. Arctic kit. Open/close indicator. Customised colours. Logo light panel.
System architecture	
	Industry standard PC (Intel Pentium 4) with Windows 2000 or XP. Host connection via TCP/IP or X.25. Q-Connect software support. EMV Level 2 approved.

Through-the-wall multi-function outdoor ATM

Related products
Q-CashLobby 25
Q-CashExterior 25
Q-Cash 45
Q-Connect
Q-Coput

About BANQIT

BANQIT develops, manufactures and markets solutions for local cash handling. BANQIT offers innovative systems based on cutting edge technology to banks, cash-in-transit companies and retailers.

BANQIT AB

Visiting address: Kronborgsgränd 19
 Mail address: P.O. Box 57
 SE-164 94 Kista, Sweden
 Telephone: +46 (0)8 759 46 00
 Fax: +46 (0)8 621 17 18
 E-mail: headoffice@banqit.com
 Web: www.banqit.com



Manufacturing of BANQIT products adheres to RoHS and CE directives and is approved according to ISO 9001 quality management standards and the ISO 14000 environmental management standards.

Every effort has been made to ensure that all information contained herein is accurate at the time of publication. Such information is subject to change without notice. BANQIT AB is not responsible for any inadvertent errors.